

INCLINOMETERS & PENDULUMS







S700





TILT BEAM SENSORS

Tilt Beam (TB) sensor consists of a MEMS tiltmeter mounted on a rigid aluminium beam with a defined gauge length, tipically 1, 2 or 3 meters. Tilt meters shall be mounted on the beams at site and are available in digital and analogue version, with uniaxial or biaxial sensor.

TB most common application is horizontal chain on structures in order to monitor differential settlements or heaves. TB can be also installed horizontally, vertically or inclined, in chains or in stand alone installations.

Thanks to the sensor fixing and adjustement plate, they could be utilized to monitor every tilting or displacement in a large number of applications.

APPLICATIONS

- Structures
- Diaphragm walls
- Dams
- Tunneling
- Deep excavations
- Unstable slopes

FEATURES

- Removable and modular
 system for multiple installation
- Simple and fast installation through connectors (digital version)
- Inclined installation allowed
- Nearly real-time monitoring with
 OMNIAlog and miniOMNIAlog

G Reet the essential requirements of the EMC Directive 2014/30/UE



S700

TILT METERS SPECIFICATIONS

PRODUCT CODES	0 S541MA0000 Uniaxial	0S542MA0000 Biaxial	0S542HD0000 Biaxial	
Measurement principle	self-compensated MEMS inclinometer		self-compensated MEMS inclinometer	
Measuring range (1)	±2.5°, ±5°, ±10°		±2.5°, ±5°, ±10°	
Sensor resolution (reading frequency 2 Hz)	0.001°		0.0001°	
Sensor mechanical bandwidth	18 Hz		1 Hz	
Sensitivity (3)	see Calibration Report		see Calibration Report	
Accuracy: MPE ⁽⁴⁾	$\pm 0.004^{\circ}$ for $\pm 2.5^{\circ}$ range $\pm 0.006^{\circ}$ for $\pm 5^{\circ}$ range $\pm 0.010^{\circ}$ for $\pm 10^{\circ}$ range		±0.002°	
Offset temperature dependency (from -20°C to +70°C)	±0.003°/°C		±0.002°/°C	
Power supply	from 18 to 30 Vdc		from 8 to 28 Vdc	
Signal output and protocol	4-20 mA current loop (inclination), Ohm (temperature)		RS485, Modbus RTU (5)	
A/D converter			32 bit, precision 38-kSPS	
Average consumption	max 20 mA per Axis		Biaxial sensor: 5.3 mA @ 24 Vdc, 10.0 mA @ 12 Vdc	
Temperature operating range	from -30°0	C to +70°C	from -30°C to +70°C	
Internal temperature sensor: - measuring range - accuracy (resolution)	- NTC 3 kΩ from -50°C ±0.5 °C (0	Thermistor to +150°C to +50°C)	Embedded on electronic board - 40°C to +125°C ±1°C with temperature range -10°C to +85°C (res. 0.01 °C)	
Internal humidity sensor: ⁽⁶⁾ - measuring range - accuracy (resolution)		-	Embedded on electronic board 0 to 100% RH ±5% RH with humidity range 0 to 95% RH (res. 0.025% RH)	
On-board supply voltage monitor: ⁽⁶⁾ - measuring range - accuracy (resolution)		-	Embedded on electronic board 0 to 36 V ±5% FS (res. 0.01 V)	
Signal cable	0WE106IP0ZH		0WE106IP0ZH	
Cabling	M12 male 8-pin conn	ector on sensor body	M12 male connector on sensor body, 3-port T-shaped splitter for cable wiring	
Max. cable length to logger	1000 m (for more information see FAQ #073) $^{\scriptscriptstyle (7)}$		1000 m (for more information see <u>FAQ #073</u>) ⁽⁷⁾	

(1) Other ranges available on request

(2) Stability calculated as difference after 30 days under repeatability conditions.

(3) Sensitivity is a specific parameter different for every gauge. The sensitivity is calculated during gauge calibration test and inserted into the Calibration Report.

(4) MPE is the Maximum Permitted Error on the measuring range (FSR). In the Calibration Report, the accuracies of the gauge are calculated using the linear regression; the error reported is the maximum residual error on the FSR.

(5) RS485 not-optoisolated Modbus communication with RTU Protocol. Default output is sen , other units available are degree, mm/m and inch/feet (to be requested at order). Sisgeo Modbus protocol manual is available for download at this page.

(6) These sensors are installed on the internal electronic board to give information in the event of probe malfunction.

(7) Refer to FAQ section on Sisgeo website: www.sisgeo.com/faq





S700

PHYSICAL FEATURES

	BEAM	TILT SENSOR	
Length	1000, 2000 or 3000 mm (L)	99 mm	
Width	44 mm	49 mm	
Height	60 mm	55 mm	
Material	aluminium	anodized aluminum	





Connection detail of analogue tilt sensor on beam trough the fixing and adjustement plate.



Detail of beam mechanical connection



ACCESSORIES AND SPARE PARTS

ALUMINIUM BEAM OS7BM000002

Aluminium beam for both analogue or digital sensors, available in different length: 1000, 2000 or 3000 mm. Supplied with topographic target, wall mounting supports at the ends and anchor bolts.

"L" MOUNTING PLATE OS7BM80SUP0

"L" shaped, floor mounting bracket for horizontal digital beam installation, realized in galvanized steel. Customized brackets for inclined analogue beam sensors available on request.

TERMINATION RESISTANCE OETERMRESIO

Resistance ending device with connector, needed to close every digital tilt meter chain. The value of resistor depends on the layout of each monitoring system. For more detail see FAQ#076.

BUILDING SETTLEMENT MONITORING EXAMPLE WITH DIGITAL TILT METERS





STRUCTURAL TILT/CANT MONITORING EXAMPLE WITH ANALOGUE TILT METERS





READABLE BY

(1)	C R D	$=$ $(1 \cdot)$		
		D READO		
	400		C] -	

(1) Only for analogue version (mod. S541MA & S542MA)

For further information refer to their own datasheets

All the information in this document is the property of Sisgeo S.r.I. and should not be used without permission from Sisgeo S.r.I. The manufacturer reserves the right to make changes to the product or to its parts without prior notice, also on the basis of contingent situations not related to the technical characteristics alone, such as, for example, material or components shortages. For the specific accuracy performance of each product, please refer to the Calibration Report issued for each instrument. The datasheet is issued in English and other languages. In order to avoid discrepancies and disagreement on the interpretation of the meanings, Sisgeo Srl declares that English Language prevails.

SISGEO S.R.L.

VIA F. SERPERO 4/F1 20060 MASATE (MI) ITALY PHONE +39 02 95764130 FAX +39 02 95762011 INF0@SISGE0.COM

ADDITIONAL SUPPORT

SISGEO offers on-line assistance service to the Customers in order to maximize the performance of the system and training on the correct use of the instrument/readout.

For more information contact mail: assistance@sisgeo.com